SB100: Video Sound Bar



Product Features

- ✓ All-in-one-design: Camera, speakers and microphones
- ✓ 120° wide angle, 4k camera, 5x digital zoom
- ✓ Android 8.0 operating system with Screenshare Pro
- ✓ 6 array MEMS microphone, 8m pickup distance
- ✓ Noise reduction, echo cancellation, dereverberation
- ✓ Dual Band WiFi
- ✓ Installation options: desktop, wall mount or mobile stand
- ✓ Perfect for PC-based video conferencing (Zoom, Microsoft Teams, Google Meet, etc.)
- ✓ Zoom Certified Device for Zoom Rooms installation

LOFT

Product Specifications

\bigcirc	naratina	Custom
U	perating	System

Main Processor 2*A73+2*A53

Memory 4GB

Flash Drive 16GB

Audio DSP RM 4*A35

System Function Wireless screenshare

Camera

Sensor Type 1/2.3, CMOS, 12.3 MP

Scanning Mode Progressive

Field of View (DFOV) 120°

Focus Mode Fixed focus

Frame Rate 4k@30fps

Tilt Range UP 15°, Down 15°

Minimal Illumination O.05 Lux @ (F1.8, AGC ON)

White Balance Auto

Digital Noise Reduction 2D digital noise reduction

Backlight Compensation Yes

Camera Mount Magnet+M12

Function EPTZ, Auto-framing

Speaker

Maximum Sound Pressure Level 86dBSPL@1m,1kHz

Frequency Range 150Hz~15kHz

Distortion ≤5%

Signal to Noise Ratio ≥75dB

Speaker Channel 1.0

Output Power 1*10W

LOFT

Microphones

Number of Microphones 6.0

Microphones Type MEMS

Voice Pickup Range 8m

Voice Pickup Angle 180 ° directly in front

Noise Reduction Yes

Echo Cancellation Yes

Wireless Microphone Compatible Yes

USB Features

Color System/Compression H.264/YUY2/MJPG

Video Format 4k@30fps/25fps, 1080p@30fps/25fps,

720p@30fps/25fps,

960x540p@30fps/25fps, 640x360p@30fps/25fps etc

USB Video Communication Protocol UVC 2.0

Input/Output Interface

Audio 1*3.5mm mic

HDMI 1*HDMI 1.4

Internet 1*RJ45 10/100Mbps

USB 1xUSB 2.0: Type C, female

1xUSB 3.0: Type A, female

DC in 1*DC 2.0

WiFi

WiFi Standard 802.11 a/b/g/n/ac

Operating Frequency 2.4G&5G

WiFi Mode AP+STA

WiFi Range Up to 10m

LOFT

Physical Specifications & Environmental Conditions

Standby Power Consumption ≤0.5W

Input Voltage 12V DC

Input Current 3A

Operating Temperature O°C ~ 40°C

Storage Temperature -20°C ~ 60°C

Humidity 10% ~ 90%

Power Consumption 20W type

Size 465mm x 91mm x 57mm

Net Weight 1300g